

Data Sheet

Electramo NV		YE3-200L1-2 - 30kW - 2965 rpm - 400V/690V				
Industrieweg 14 B-2390 Malle Belgium +32 3 311 65 40 info@electramo.com www.electramo.com BE 0414.941.452		Electric motor Type IEC60034-30				
Efficiencies		IE3 (Premium Efficiency)				
Insulation class		F / B				
Temperatures		-20°C / +40°C				
Connection - Phases		Δ	Y	Δ	Δ	Δ
Tension	V	400	690	440	460	480
Frequency	Hz	50	50	60	60	60
Output	kW	30,00	30,00	36,00	36,00	36,00
Speed	min⁻¹	2.965	2965	3558	3558	3558
Current	A	52,14	30,23	56,88	54,41	52,14
Efficiency	%	100%	75%	50%		
		93,30	93,20	92,10		
Cos φ		100%	75%	50%		
		0,89	0,89	0,82		
Starting Current	A	7,60	I _a /I _n			
No Load Current	A	14,52	400V 50Hz			
Nominal Torque	Nm	96,62	Nm			
Starting Torque	Nm	2,00	M _s /M _n			
Maximum torque	Nm	2,30	M _{max} /M _n			
Construction		Cast Iron				
Mounting position		B3 - IM1001 - feet - horizontal				
Protection		IP 55				
Cooling method		IC 411				
Duty type		S1				
Tropical treatment		95%				
Max. altitude A.S.L.		1000 m				
Paint (body / fan cover)		RAL 7030				
Terminal Box Position		Top - A1				
Cable entries		2 x M50x1,5 + 1 x M16x1,5				
Direction of rotation		← / →				
Drain hole(s)		Lowest point - with plug				
Bearing DE		6312 ZZ C3				
Bearing NDE		6312 ZZ C3				
Shaft dimensions	mm	55 x 110				
Oilseals DE / NDE	mm	60 x 80 x 5,5	60 x 80 x 5,5			
Balancing (Class)		Half Key			A (IEC 60034-14)	
Sound level - L(p)A	dB(A)	76,0	50Hz - at 1m - no load			
Weight	Kg	298,1				
Options & Extras		PTC				

Every care has been taken to ensure the accuracy of the information contained in this document. Due to our policy of continuous development and improvement, Electramo reserves the right to supply products which may differ from those illustrated and described in this document. Descriptions and technical features listed in this document may not be considered as binding. Under no circumstances should data in this document be considered as a contractual obligation.