

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Data sheet for three-phase Squirrel-Cage-Motors



Motor type / Motor type : 1CV3205B

SIMOTICS SD - 200 L - IM B35 - 4p

Client order no. / Client order no.	Item-No. / Item-No.	Offer no. / Offer no.
Order no. / Order no.	Consignment no. / Consignment no.	Project / Project

Remarks / Remarks

Safe Area

-/-

Electrical data / Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N I_f/I_N	M_A/M_N T_f/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
DOL duty (S1) / DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	30.00	-/-	55.00	1470	195.0	93.6	94.0	93.7	0.84	0.80	0.71	7.3	2.6	3.1	IE3
690	Y	50	30.00	-/-	32.00	1470	195.0	93.6	94.0	93.7	0.84	0.80	0.71	7.3	2.6	3.1	IE3
460	Δ	60	34.50	-/-	55.00	1770	186.0	93.0	93.3	92.9	0.85	0.81	0.73	7.3	2.4	3.0	IE2
460	Δ	60	30.00	-/-	48.00	1778	161.0	94.1	94.2	93.6	0.83	0.79	0.70	8.8	2.6	3.5	IE3
IM B35 / IM 2001		FS 200 L		IP55		UKCA		IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions / Environmental conditions : -20 °C - +40 °C / 1000 m Locked rotor time (hot / cold) / Locked rotor time (hot / cold) : 29.4 s | 45 s

Mechanical data / Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz Sound level (SPL / SWL) at 50Hz 60Hz	65 / 72 dB(A) ^{2) 3)}	67 / 74 dB(A) ^{2) 3)}	Vibration severity grade Vibration severity grade	A A
Moment of inertia Moment of inertia	0.2400 kg m ²		Thermal class Thermal class	F F
Bearing DE NDE Bearing DE NDE	6212 2Z C3	6212 2Z C3	Duty type Duty type	S1
bearing lifetime / bearing lifetime			Direction of rotation Direction of rotation	bidirectional bidirectional
L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material Frame material	cast iron cast iron
L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾			Net weight of the motor (IM B3) Net weight of the motor (IM B3)	240 kg
Regreasing device Regreasing device	Without Without		Coating (paint finish) Coating (paint finish)	Standard paint finish C2 Standard paint finish C2
Grease nipple Grease nipple	-/-		Color, paint shade Color, paint shade	RAL7030
Type of bearing Type of bearing	Locating bearing NDE Locating bearing NDE		Motor protection Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals) (B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes Condensate drainage holes	With (standard) With (standard)		Method of cooling Method of cooling	IC411 - self ventilated, surface cooled IC411 - self ventilated, surface cooled
External earthing terminal External earthing terminal	With (standard) With (standard)			

Terminal box / Terminal box

Terminal box position Terminal box position	top	Max. cross-sectional area Max. cross-sectional area	25 mm ²
Material of terminal box Material of terminal box	cast iron cast iron	Cable diameter from ... to ... Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box Type of terminal box	TB1 L01	Cable entry Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread Contact screw thread	M6	Cable gland Cable gland	4 plugs 4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal 1) L_{10mh} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
 M_A/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
 M_K/M_N = break down torque / nominal torque

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet	document status released			
	title 1LE1503-2AB53-4JB4	document number			
© INMOTICS 2024	rev. 953	creation date 2024-02-16	language en/en	Page 1/1	