

Data Sheet

Electramo NV Industrieweg 14 B-2390 Malle Belgium +32 3 311 65 40 info@electramo.com www.electramo.com BE 0414.941.452	Electric motor Type Efficiencies Insulation class Temperatures Connection - Phases Tension V Frequency Hz Output kW Speed min⁻¹ Current A Efficiency % Cos φ Starting Current A No Load Current A Nominal Torque Nm Starting Torque Nm Maximum torque Nm Construction Mounting position Protection Cooling method Duty type Tropical treatment Max. altitude A.S.L. Paint (body / fan cover) Terminal Box Position Cable entries Direction of rotation Drain hole(s) Bearing DE Bearing NDE Shaft dimensions mm Oilseals DE / NDE mm Balancing (Class) Sound level - L(p)A dB(A) Weight Kg Options & Extras	YE3-250M-2 - 55kW - 2975 rpm - 400V/690V IEC60034-30 IE3 (Premium Efficiency) F / B -20°C / +40°C <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;"></th> <th style="width: 15%; text-align: center;">Δ</th> <th style="width: 15%; text-align: center;">Y</th> <th style="width: 15%; text-align: center;">Δ</th> <th style="width: 15%; text-align: center;">Δ</th> <th style="width: 15%; text-align: center;">Δ</th> </tr> </thead> <tbody> <tr> <td></td> <td style="text-align: center;">400</td> <td style="text-align: center;">690</td> <td style="text-align: center;">440</td> <td style="text-align: center;">460</td> <td style="text-align: center;">480</td> </tr> <tr> <td></td> <td style="text-align: center;">50</td> <td style="text-align: center;">50</td> <td style="text-align: center;">60</td> <td style="text-align: center;">60</td> <td style="text-align: center;">60</td> </tr> <tr> <td></td> <td style="text-align: center;">55,00</td> <td style="text-align: center;">55,00</td> <td style="text-align: center;">66,00</td> <td style="text-align: center;">66,00</td> <td style="text-align: center;">66,00</td> </tr> <tr> <td></td> <td style="text-align: center;">2.975</td> <td style="text-align: center;">2975</td> <td style="text-align: center;">3570</td> <td style="text-align: center;">3570</td> <td style="text-align: center;">3570</td> </tr> <tr> <td></td> <td style="text-align: center;">93,54</td> <td style="text-align: center;">54,22</td> <td style="text-align: center;">102,04</td> <td style="text-align: center;">97,60</td> <td style="text-align: center;">93,54</td> </tr> <tr> <td></td> <td style="text-align: center;">100%</td> <td style="text-align: center;">75%</td> <td style="text-align: center;">50%</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">94,30</td> <td style="text-align: center;">94,10</td> <td style="text-align: center;">93,00</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">100%</td> <td style="text-align: center;">75%</td> <td style="text-align: center;">50%</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0,90</td> <td style="text-align: center;">0,88</td> <td style="text-align: center;">0,82</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">7,70</td> <td style="text-align: center;">Ia/In</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">25,84</td> <td style="text-align: center;">400V 50Hz</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">176,55</td> <td style="text-align: center;">Nm</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">2,00</td> <td style="text-align: center;">Ms/Mn</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">2,30</td> <td style="text-align: center;">Mmax/Mn</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="5">Cast Iron</td> </tr> <tr> <td></td> <td colspan="5">B3 - IM1001 - feet - horizontal</td> </tr> <tr> <td></td> <td colspan="5">IP 55</td> </tr> <tr> <td></td> <td colspan="5">IC 411</td> </tr> <tr> <td></td> <td colspan="5">S1</td> </tr> <tr> <td></td> <td colspan="5">95%</td> </tr> <tr> <td></td> <td colspan="5">1000 m</td> </tr> <tr> <td></td> <td colspan="5">RAL 7030</td> </tr> <tr> <td></td> <td colspan="5">Top - A1</td> </tr> <tr> <td></td> <td colspan="5">2 x M63x1,5 + 1 x M16x1,5</td> </tr> <tr> <td></td> <td colspan="5">← / →</td> </tr> <tr> <td></td> <td colspan="5">Lowest point - with plug</td> </tr> <tr> <td></td> <td colspan="5">6314 C3</td> </tr> <tr> <td></td> <td colspan="5">6314 C3</td> </tr> <tr> <td></td> <td style="text-align: center;">60 x 140</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">70 x 90 x 5,5</td> <td></td> <td style="text-align: center;">70 x 90 x 5,5</td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="2">Half Key</td> <td colspan="3">A (IEC 60034-14)</td> </tr> <tr> <td></td> <td style="text-align: center;">81,0</td> <td colspan="4" style="text-align: center;">50Hz - at 1m - no load</td> </tr> <tr> <td></td> <td colspan="5">482,8</td> </tr> <tr> <td></td> <td colspan="5">PTC</td> </tr> </tbody> </table>		Δ	Y	Δ	Δ	Δ		400	690	440	460	480		50	50	60	60	60		55,00	55,00	66,00	66,00	66,00		2.975	2975	3570	3570	3570		93,54	54,22	102,04	97,60	93,54		100%	75%	50%				94,30	94,10	93,00				100%	75%	50%				0,90	0,88	0,82				7,70	Ia/In					25,84	400V 50Hz					176,55	Nm					2,00	Ms/Mn					2,30	Mmax/Mn					Cast Iron						B3 - IM1001 - feet - horizontal						IP 55						IC 411						S1						95%						1000 m						RAL 7030						Top - A1						2 x M63x1,5 + 1 x M16x1,5						← / →						Lowest point - with plug						6314 C3						6314 C3						60 x 140						70 x 90 x 5,5		70 x 90 x 5,5				Half Key		A (IEC 60034-14)				81,0	50Hz - at 1m - no load					482,8						PTC				
	Δ	Y	Δ	Δ	Δ																																																																																																																																																																																																															
	400	690	440	460	480																																																																																																																																																																																																															
	50	50	60	60	60																																																																																																																																																																																																															
	55,00	55,00	66,00	66,00	66,00																																																																																																																																																																																																															
	2.975	2975	3570	3570	3570																																																																																																																																																																																																															
	93,54	54,22	102,04	97,60	93,54																																																																																																																																																																																																															
	100%	75%	50%																																																																																																																																																																																																																	
	94,30	94,10	93,00																																																																																																																																																																																																																	
	100%	75%	50%																																																																																																																																																																																																																	
	0,90	0,88	0,82																																																																																																																																																																																																																	
	7,70	Ia/In																																																																																																																																																																																																																		
	25,84	400V 50Hz																																																																																																																																																																																																																		
	176,55	Nm																																																																																																																																																																																																																		
	2,00	Ms/Mn																																																																																																																																																																																																																		
	2,30	Mmax/Mn																																																																																																																																																																																																																		
	Cast Iron																																																																																																																																																																																																																			
	B3 - IM1001 - feet - horizontal																																																																																																																																																																																																																			
	IP 55																																																																																																																																																																																																																			
	IC 411																																																																																																																																																																																																																			
	S1																																																																																																																																																																																																																			
	95%																																																																																																																																																																																																																			
	1000 m																																																																																																																																																																																																																			
	RAL 7030																																																																																																																																																																																																																			
	Top - A1																																																																																																																																																																																																																			
	2 x M63x1,5 + 1 x M16x1,5																																																																																																																																																																																																																			
	← / →																																																																																																																																																																																																																			
	Lowest point - with plug																																																																																																																																																																																																																			
	6314 C3																																																																																																																																																																																																																			
	6314 C3																																																																																																																																																																																																																			
	60 x 140																																																																																																																																																																																																																			
	70 x 90 x 5,5		70 x 90 x 5,5																																																																																																																																																																																																																	
	Half Key		A (IEC 60034-14)																																																																																																																																																																																																																	
	81,0	50Hz - at 1m - no load																																																																																																																																																																																																																		
	482,8																																																																																																																																																																																																																			
	PTC																																																																																																																																																																																																																			

Every care has been taken to ensure the accuracy of the information contained in this document. Due to our policy of continuous development and improvement, Electramo reserves the right to supply products which may differ from those illustrated and described in this document. Descriptions and technical features listed in this document may not be considered as binding. Under no circumstances should data in this document be considered as a contractual obligation.