



Ordering data: **1LE1003-1DB23-4AB4-Z**  
L22

Motor type: **1AV3162B**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I <sub>A</sub> /I <sub>N</sub> I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>A</sub> /T <sub>N</sub>	M <sub>k</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	11.00	- / -	20.50	1475	71.0	91.4	91.9	91.4	0.84	0.80	0.70	6.8	2.2	3.2	IE3
690	Y	50	11.00	- / -	12.00	1475	71.0	91.4	91.9	91.4	0.84	0.80	0.70	6.8	2.2	3.2	IE3
460	Δ	60	12.60	- / -	20.00	1775	68.0	92.4	92.7	92.1	0.85	0.81	0.73	7.1	2.0	3.2	IE3
460	Δ	60	11.00	- / -	18.00	1780	59.0	92.4	92.4	91.3	0.83	0.78	0.68	7.9	2.3	3.7	IE3
IM B3 / IM 1001		FS 160 M		83 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

These values are calculated. The final rating plate data will be calculated when the order is placed  
The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data		Terminal box	
Sound pressure level 50Hz/60Hz (load)	65 dB(A)   69 dB(A)	Terminal box position	top
Moment of inertia	0.083 kg m <sup>2</sup>	Material of terminal box	Aluminium
Bearing DE   NDE	6309 2ZC3   6209 2ZC3	Type of terminal box	TB1 J00
Bearing lifetime	40000 h	Contact screw thread	M5
Lubricants	Esso Unirex N3	Max. cross-sectional area	16.0 mm <sup>2</sup>
Regreasing device	No	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Grease nipple	- / -	Cable entry	2xM40x1,5-1xM16x1,5
Type of bearing	Locating bearing NDE	Cable gland	3 plugs
Condensate drainage holes	No	<div style="border: 1px solid black; padding: 5px; text-align: center;"> <b>Special design</b>                      L22 Bearing design for increased cantilever forces                 </div>	
External earthing terminal	No		
Vibration class	A		
Insulation	155(F) to 130(B)		
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	aluminum		
Data of anti condensation heating	- / -		
Coating	Standard paint finish C2		
Color	RAL7030		
Motor protection	(B) 3 PTC thermistors - for tripping		
Method of cooling	IC411 - self ventilated, surface cooled		

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m